

DB NAME : DB-Tuck 2
TYPE : Surface MOUNTED
COLOUR : WHITE
IP RATING : IN DOOR

FEED FROM MAIN KIOSK

25MM² 4CORE PVC PVC SWA PVC CABLE
16MM² BCEW

63A
C/B

230V 63A

SPFN

NDRMAL POWER

15A 15A 15A 15A 15A 15A
5KA 5KA 5KA 5KA 5KA 5KA

63A
EL

30A 30A 30A 20A
5KA 5KA 5KA 5KA

20A 20A 20A
5KA 5KA 5KA

CIRCUIT NUMBER	L1	L2	L3	L4	L5	Spare	P1	P2	Spare	ISD	ISD	ISD	ISD
CONDUCTOR SIZE IN mm ²		2.5mm ²					4mm ²			4mm ²			
EARTH CONDUCTOR SIZE IN mm ²		2.5mm ²					4mm ²			4mm ²			
CONDUIT IN mm		25mm					25mm			25mm			
LABEL	1	2	3	4	5	6	7	8	9	10	11	12	13
EQUIPMENT	LIGHTS						SSD			ISOLATOR			

NOTES: 1) FRONT ACCESS ONLY

DRAWING

NORMAL POWER

PROJECT JL DUBE

DWG.No.T1/01/0.A3/R1363/DB/02

SHEET 1 of 1

DATE 28/08/2020

DRAW AUTOCAD

REV

1

CONSULTING ENGINEERS

RISIMATI
ENGINEERS

MECHANICAL, ELECTRICAL AND CIVIL SERVICES
759 Blue Ash Street
Novosibirsk, Russia, 630090
P.O. Box 15504, Harbin, 150085
Tel: +86 903 888 0051
Fax: +86 903 888 0052
E-mail: sarfraz@risimati.com